



300 Mears Boulevard
Oldsmar, FL 34677

Ph: (813) 891-1313

Fax: (813) 891-9988

www.allcases.com

support@allcases.com

FEATURES

- Durable GMT (Glass Mat Thermoplastic) Composite Case Exterior
- Shock and Vibration protection for 40 - 80G
- Slide-Out Riveted Aluminum CEA 310 Rack with a Minimum of Eight Multi-Axis Shock Mounts
- 10-32 Nut-Bar Fasteners for Optional Equipment Panels
- Two 3" Removable Covers Standard. 5" Lids available for 3U to 9U cases.
- External Draw Pull Latches
- Watertight Closure provides protection from moisture, salt spray, sand and dust
- Molded-in, Case-to-Case Stacking Standard
- Recessed Stainless Steel Latches
- Case shell performance temperature range of -65 / 185 F (-54 / 85 C)
- Designed for Equipment Weights up to 120 lbs (54.4 kg) Standard
- May be Custom Reinforced to Accommodate Equipment Weights up to 180 lbs (81.6 kg)
- Available in Black, Desert Tan, or OD Green with black oxide stainless steel latches

ABOUT ALLCASES

- Established in 1985
- Small Business
- Woman Owned
- AS9100:2009 Certified
- ISO9001:2009 Certified
- GSA Contract Available



COMPOSITE RACKMOUNT CASES

LIGHTWEIGHT, COMPACT, HI-PERFORMANCE RACK ENCLOSURES

Allcases Composite Rackmount Cases provide exceptional equipment protection with the utility of slide-mounted racks, which allow unlimited access to electronic equipment. The Composite Rackmount Case series features a strong GMT (Glass Mat Thermoplastic) case shell. The GMT shell is exceptionally stiff, lightweight, high impact-absorbing and can perform in extreme temperature ranges.

Allcases Composite Rackmount Cases are certified to MIL-STD-810F and comply with MIL-STD-810G performance testing for electronic enclosures to withstand the effects of the harshest environments.

AVAILABLE SIZES

| Rack U Size | Product # | External Dimensions (HxWxD) | Rack Depth | Total Weight (lbs) |
|-------------|--------------|-----------------------------|------------|--------------------|
| 3U | REPH2400-3U | 9.57" x 22.53" x 30.00" | 20.00" | 38.4 |
| | REPH2800-3U | 9.57" x 22.53" x 34.50" | 24.00" | 40.1 |
| | REPH3400-3U | 9.57" x 22.53" x 40.14" | 30.00" | 49.1 |
| 4U | REPH2400-4U | 11.32" x 22.53" x 30.00" | 20.00" | 39.9 |
| | REPH2800-4U | 11.32" x 22.53" x 34.50" | 24.00" | 41.8 |
| | REPH3400-4U | 11.32" x 22.53" x 40.14" | 30.00" | 50.8 |
| 5U | REPH2400-5U | 13.07" x 22.53" x 30.00" | 20.00" | 42.0 |
| | REPH2800-5U | 13.07" x 22.53" x 34.50" | 24.00" | 43.9 |
| | REPH3400-5U | 13.07" x 22.53" x 40.14" | 30.00" | 52.4 |
| 6U | REPH2400-6U | 14.82" x 22.53" x 30.00" | 20.00" | 45.5 |
| | REPH2800-6U | 14.82" x 22.53" x 34.50" | 24.00" | 47.4 |
| | REPH3400-6U | 14.82" x 22.53" x 40.14" | 30.00" | 54.2 |
| 7U | REPH2400-7U | 16.57" x 22.53" x 30.00" | 20.00" | 47.9 |
| | REPH2800-7U | 16.57" x 22.53" x 34.50" | 24.00" | 49.8 |
| | REPH3400-7U | 16.57" x 22.53" x 40.14" | 30.00" | 55.7 |
| 8U | REPH2400-8U | 18.32" x 22.53" x 30.00" | 20.00" | 49.7 |
| | REPH2800-8U | 18.32" x 22.53" x 34.50" | 24.00" | 51.5 |
| | REPH3400-8U | 18.32" x 22.53" x 40.14" | 30.00" | 57.4 |
| 9U | REPH2400-9U | 20.07" x 22.53" x 30.00" | 20.00" | 51.9 |
| | REPH2800-9U | 20.07" x 22.53" x 34.50" | 24.00" | 53.6 |
| | REPH3400-9U | 20.07" x 22.53" x 40.14" | 30.00" | 60.8 |
| 10U | REPH2400-10U | 21.82" x 22.53" x 30.00" | 20.00" | 53.9 |
| | REPH2800-10U | 21.82" x 22.53" x 34.50" | 24.00" | 55.6 |
| 11U | REPH2400-11U | 23.57" x 22.53" x 30.00" | 20.00" | 56.1 |
| | REPH2800-11U | 23.57" x 22.53" x 34.50" | 24.00" | 57.7 |
| 12U | REPH2400-12U | 25.32" x 22.53" x 30.00" | 20.00" | 58.3 |
| | REPH2800-12U | 25.32" x 22.53" x 34.50" | 24.00" | 59.8 |
| 13U | REPH2400-13U | 27.07" x 22.53" x 30.00" | 20.00" | 60.5 |
| | REPH2800-13U | 27.07" x 22.53" x 34.50" | 24.00" | 61.9 |
| 14U | REPH2400-14U | 28.82" x 22.53" x 30.00" | 20.00" | 62.8 |
| | REPH2800-14U | 28.82" x 22.53" x 34.50" | 24.00" | 64.0 |

Outside Dimensions are for (2) 3" Lids. 5" Lids available for 3U to 9U.